



H05V-K

Application and Description

These insulated wires are determined for installation to the inside of apparatus as well as for the protective laying to the lightings, in dry rooms, in production facilities, switch and distributors boards, in tubes, under and surface mounting of plasters.

Standard and Approval

NF C 32-201-3, CE Low Voltage Directive 73/23/EEC and 93/68/EEC, ROHS compliant

Cable Construction


- Fine bare copper strands
- Strands to VDE-0295 Class-5, IEC 60228 Class-5
- Special PVC TI1 core insulation
- Cores to VDE-0293 colors on chart

Technical Characteristics

- Working voltage: 300/500v
- Test voltage: 2000 volts
- Flexing bending radius: 12.5 x Ø
- Static bending radius: 12.5 x Ø
- Flexing temperature: -5° C to +70° C
- Static temperature: -30° C to +80° C
- Flame retardant: NF C 32-070
- Insulation resistance: 10 MΩ x km



H05V-K



Bare copper conductor

PVC insulation

H05V-K

Cable Parameter

| AWG | No. of Cores x Nominal Cross Sectional Area # x mm ² | Nominal Thickness of Insulation mm | Nominal Overall Diameter mm | Nominal Copper Weight kg/km | Nominal Weight kg/km |
|-----------|--|---|--------------------------------------|-----------------------------------|----------------------------|
| 20(16/32) | 1 x 0.5 | 0,6 | 2.1 | 4.9 | 10 |
| 18(24/32) | 1 x 0.75 | 0,6 | 2.4 | 7.2 | 13 |
| 17(32/32) | 1 x 1 | 0,6 | 2.6 | 9.6 | 15 |